

E-PROPS 3-blade Fixed Pitch models

Reference	Diameter in cm	Weight in g	Setting at 75 % in deg	Pitch at 75 % in cm
3-T-32-115	115 cm	660 gr	13,4°	65 cm
3-T-33-115	115 cm	660 gr	14,3°	69 cm
3-T-34-115	115 cm	660 gr	15,2°	74 cm
3-T-35-115	115 cm	660 gr	16,0°	78 cm
3-T-52-115	115 cm	720 gr	14,5°	70 cm
3-T-53-115	115 cm	720 gr	15,4°	75 cm
3-T-54-115	115 cm	720 gr	16,2°	79 cm
3-T-55-115	115 cm	720 gr	17,1°	83 cm
3-T-72-115	115 cm	780 gr	17,2°	84 cm
3-T-73-115	115 cm	780 gr	18,0°	88 cm
3-T-74-115	115 cm	780 gr	18,9°	93 cm
3-T-75-115	115 cm	780 gr	19,8°	98 cm
3-T-76-115	115 cm	780 gr	20,7°	102 cm
3-T-77-115	115 cm	780 gr	21,5°	107 cm
3-T-32-120	120 cm	660 gr	13,1°	66 cm
3-T-33-120	120 cm	660 gr	14,0°	70 cm
3-T-34-120	120 cm	660 gr	14,9°	75 cm
3-T-35-120	120 cm	660 gr	15,7°	79 cm
3-T-52-120	120 cm	720 gr	14,1°	71 cm
3-T-53-120	120 cm	720 gr	15,0°	76 cm
3-T-54-120	120 cm	720 gr	15,8°	80 cm
3-T-55-120	120 cm	720 gr	16,7°	85 cm
3-T-72-120	120 cm	780 gr	16,6°	84 cm
3-T-73-120	120 cm	780 gr	17,4°	89 cm
3-T-74-120	120 cm	780 gr	18,3°	94 cm
3-T-75-120	120 cm	780 gr	19,2°	98 cm
3-T-76-120	120 cm	780 gr	20,1°	103 cm
3-T-77-120	120 cm	780 gr	20,9°	108 cm
3-T-32-125	125 cm	660 gr	12,7°	66 cm
3-T-33-125	125 cm	660 gr	13,6°	71 cm

E-PROPS 3-blade Fixed Pitch models

Reference	Diameter in cm	Weight in g	Setting at 75 % in deg	Pitch at 75 % in cm
3-T-32-115	115 cm	660 gr	13,4°	65 cm
3-T-33-115	115 cm	660 gr	14,3°	69 cm
3-T-34-125	125 cm	660 gr	14,5°	76 cm
3-T-35-125	125 cm	660 gr	15,4°	81 cm
3-T-52-125	125 cm	720 gr	13,8°	72 cm
3-T-53-125	125 cm	720 gr	14,6°	77 cm
3-T-54-125	125 cm	720 gr	15,5°	82 cm
3-T-55-125	125 cm	720 gr	16,4°	87 cm
3-T-72-125	125 cm	780 gr	16,0°	84 cm
3-T-73-125	125 cm	780 gr	16,9°	89 cm
3-T-74-125	125 cm	780 gr	17,7°	94 cm
3-T-75-125	125 cm	780 gr	18,6°	99 cm
3-T-76-125	125 cm	780 gr	19,5°	104 cm
3-T-77-125	125 cm	780 gr	20,4°	110 cm
3-T-32-130	130 cm	660 gr	12,2°	66 cm
3-T-33-130	130 cm	660 gr	13,1°	71 cm
3-T-34-130	130 cm	660 gr	14,0°	76 cm
3-T-35-130	130 cm	660 gr	14,9°	82 cm
3-T-52-130	130 cm	720 gr	13,4°	73 cm
3-T-53-130	130 cm	720 gr	14,3°	78 cm
3-T-54-130	130 cm	720 gr	15,1°	83 cm
3-T-55-130	130 cm	720 gr	16,0°	88 cm
3-T-72-130	130 cm	780 gr	15,4°	84 cm
3-T-73-130	130 cm	780 gr	16,3°	90 cm
3-T-74-130	130 cm	780 gr	17,2°	95 cm
3-T-75-130	130 cm	780 gr	18,1°	100 cm
3-T-76-130	130 cm	780 gr	18,9°	105 cm
3-T-77-130	130 cm	780 gr	19,8°	110 cm
3-T-42-135	135 cm	750 gr	13,4°	76 cm
3-T-43-135	135 cm	750 gr	14,3°	81 cm

E-PROPS 3-blade Fixed Pitch models

Reference	Diameter in cm	Weight in g	Setting at 75 % in deg	Pitch at 75 % in cm
3-T-32-115	115 cm	660 gr	13,4°	65 cm
3-T-33-115	115 cm	660 gr	14,3°	69 cm
3-T-44-135	135 cm	750 gr	15,2°	86 cm
3-T-45-135	135 cm	750 gr	16,0°	91 cm
3-T-62-135	135 cm	810 gr	14,8°	84 cm
3-T-63-135	135 cm	810 gr	15,7°	89 cm
3-T-64-135	135 cm	810 gr	16,6°	95 cm
3-T-65-135	135 cm	810 gr	17,5°	100 cm
3-T-66-135	135 cm	810 gr	18,3°	105 cm
3-T-67-135	135 cm	810 gr	19,2°	111 cm
3-T-42-140	140 cm	750 gr	13,0°	76 cm
3-T-43-140	140 cm	750 gr	13,9°	82 cm
3-T-44-140	140 cm	750 gr	14,8°	87 cm
3-T-45-140	140 cm	750 gr	15,7°	93 cm
3-T-62-140	140 cm	810 gr	14,4°	85 cm
3-T-63-140	140 cm	810 gr	15,3°	90 cm
3-T-64-140	140 cm	810 gr	16,2°	96 cm
3-T-65-140	140 cm	810 gr	17,1°	101 cm
3-T-66-140	140 cm	810 gr	17,9°	107 cm
3-T-67-140	140 cm	810 gr	18,8°	112 cm
3-T-42-145	145 cm	870 gr	13,9°	85 cm
3-T-43-145	145 cm	870 gr	14,7°	90 cm
3-T-44-145	145 cm	870 gr	15,6°	95 cm
3-T-45-145	145 cm	870 gr	16,5°	101 cm
3-T-62-145	145 cm	930 gr	15,6°	95 cm
3-T-63-145	145 cm	930 gr	16,5°	101 cm
3-T-64-145	145 cm	930 gr	17,4°	107 cm
3-T-65-145	145 cm	930 gr	18,3°	113 cm
3-T-82-145	145 cm	990 gr	17,6°	108 cm
3-T-83-145	145 cm	990 gr	18,5°	114 cm

E-PROPS 3-blade Fixed Pitch models

Reference	Diameter in cm	Weight in g	Setting at 75 % in deg	Pitch at 75 % in cm
3-T-32-115	115 cm	660 gr	13,4°	65 cm
3-T-33-115	115 cm	660 gr	14,3°	69 cm
3-T-84-145	145 cm	990 gr	19,4°	120 cm
3-T-85-145	145 cm	990 gr	20,3°	126 cm
3-T-86-145	145 cm	990 gr	21,1°	132 cm
3-T-87-145	145 cm	990 gr	22,0°	138 cm
3-T-42-150	150 cm	870 gr	13,6°	86 cm
3-T-43-150	150 cm	870 gr	14,5°	91 cm
3-T-44-150	150 cm	870 gr	15,4°	97 cm
3-T-45-150	150 cm	870 gr	16,2°	103 cm
3-T-62-150	150 cm	930 gr	15,3°	97 cm
3-T-63-150	150 cm	930 gr	16,1°	102 cm
3-T-64-150	150 cm	930 gr	17,0°	108 cm
3-T-65-150	150 cm	930 gr	17,9°	114 cm
3-T-82-150	150 cm	990 gr	17,3°	110 cm
3-T-83-150	150 cm	990 gr	18,1°	116 cm
3-T-84-150	150 cm	990 gr	19,0°	122 cm
3-T-85-150	150 cm	990 gr	19,9°	128 cm
3-T-86-150	150 cm	990 gr	20,8°	134 cm
3-T-87-150	150 cm	990 gr	21,6°	140 cm
3-T-42-155	155 cm	870 gr	13,3°	86 cm
3-T-43-155	155 cm	870 gr	14,2°	92 cm
3-T-44-155	155 cm	870 gr	15,0°	98 cm
3-T-45-155	155 cm	870 gr	15,9°	104 cm
3-T-62-155	155 cm	930 gr	14,9°	97 cm
3-T-63-155	155 cm	930 gr	15,8°	103 cm
3-T-64-155	155 cm	930 gr	16,7°	110 cm
3-T-65-155	155 cm	930 gr	17,5°	115 cm
3-T-82-155	155 cm	990 gr	16,9°	111 cm
3-T-83-155	155 cm	990 gr	17,8°	117 cm

E-PROPS 3-blade Fixed Pitch models

Reference	Diameter in cm	Weight in g	Setting at 75 % in deg	Pitch at 75 % in cm
3-T-32-115	115 cm	660 gr	13,4°	65 cm
3-T-33-115	115 cm	660 gr	14,3°	69 cm
3-T-84-155	155 cm	990 gr	18,7°	124 cm
3-T-85-155	155 cm	990 gr	19,5°	129 cm
3-T-86-155	155 cm	990 gr	20,4°	136 cm
3-T-87-155	155 cm	990 gr	21,3°	142 cm
3-T-42-160	160 cm	870 gr	13,0°	87 cm
3-T-43-160	160 cm	870 gr	13,8°	93 cm
3-T-44-160	160 cm	870 gr	14,7°	99 cm
3-T-45-160	160 cm	870 gr	15,6°	105 cm
3-T-62-160	160 cm	930 gr	14,5°	97 cm
3-T-63-160	160 cm	930 gr	15,4°	104 cm
3-T-64-160	160 cm	930 gr	16,3°	110 cm
3-T-65-160	160 cm	930 gr	17,2°	117 cm
3-T-82-160	160 cm	990 gr	16,5°	112 cm
3-T-83-160	160 cm	990 gr	17,4°	118 cm
3-T-84-160	160 cm	990 gr	18,3°	125 cm
3-T-85-160	160 cm	990 gr	19,2°	131 cm
3-T-86-160	160 cm	990 gr	20,0°	137 cm
3-T-87-160	160 cm	990 gr	20,9°	144 cm